

## ONE STRIKE LIGHTWEIGHT FILLER

One Strike Lightweight Filler is a ready mixed lightweight filler ideal for repairing surfaces prior to painting or decorating. It will not crack even at thicknesses of 75mm and is easy to apply, leaving a smooth finish. Can be over painted in 30 minutes, but at 5mm thickness and above leave to dry for at least 1-2 hours.

### Characteristics & Advantages

- Water Based
- Non-Flammable
- Low Odour
- Non shrink
- Internal or External Use
- Ready for Use
- Overpaintable
- Dries brilliant white

### Application

Prior to application the areas must be clean, dry, sound and any traces of oil or grease must be removed. If required, use masking tape along any edges but remove within 5 minutes of application.

Gun or apply directly from the tub the One Part flexible filler firmly into the crack, gap or area of repair. Ensure no air is trapped behind. Allow to dry thoroughly before overcoating with emulsion paints.



### Technical Data

|                                 |  |
|---------------------------------|--|
| <b>Material</b>                 | Water based acrylic filler                           |
| <b>Mixing Ratio</b>             | As supplied in 310ml cartridge                       |
| <b>Touch Dry</b>                | 30 minutes @ 20°C                                    |
| <b>Overcoatable</b>             | 2 hours @ 20°C for emulsion paint                    |
| <b>Minimum Application Temp</b> | 5°C  |
| <b>Joint Width - Maximum</b>    | 50mm   |
| <b>Joint Depth - Maximum</b>    | 75mm   |
| <b>Application Temperature</b>  | 5°C - 30°C   |
| <b>Density</b>                  | 0.5g/cc  |
| <b>Solids Content</b>           | Approx 60%   |
| <b>Storage</b>                  | Do not allow to freeze<br>Store between 5°C and 25°C |

### Important

The information and recommendations provided are given in good faith based on our current knowledge and experience. However, the differences in substrates, materials and site conditions are such that no warranty or fitness for a particular purpose can be inferred from this information or any written recommendations. The user must test the product's suitability for the intended use.

