

ONE PART FILLER

One Part filler is an easy to use ready mixed filler with quick drying properties. One Part filler dries to a smooth, tough crack resistant finish, is easily sandable and may be painted or stained. Suitable for both internal and external use.

Characteristics & Advantages

- Water Based
- Non-Flammable
- Low Odour
- Non Hazardous
- Internal or External Use
- Ready for Use
- Dries white
- Quick drying

Application

Prior to application the areas must be clean, dry, sound and any traces of oil or grease must be removed. If required, use masking tape along any edges but remove within 5 minutes of application.

Apply the One Part filler firmly into the crack, gap or area of repair. Ensure no air is trapped behind. Allow to dry for 10 minutes for minor imperfections, longer times are required dependent on the filling depth. Overpaintable after drying with most solvent based and emulsion paints. If used externally, prevent contact with water for at least 5 hours.



Technical Data

Material	Water based acrylic filler
Mixing Ratio	As supplied
Drying	1 – 8 hours depending on depth and temperature
Minimum Application Temp	5°C
Maximum Fill	5 mm in one coat – further layers may be built up
Maximum Depth	25mm

Important

The information and recommendations provided are given in good faith based on our current knowledge and experience. However, the differences in substrates, materials and site conditions are such that no warranty or fitness for a particular purpose can be inferred from this information or any written recommendations. The user must test the product's suitability for the intended use.

